



Technical data

1. Nominal voltage: 150V/8A
PITCH: 3.5mm
2. Insulation Withstands Voltage:
AC 1300V/MIN
3. Insulation Resistance:
1000M Ω or more at DC500V
4. Using temperature range: -40C ~ 115C
5. Undimensioned Tolerances:

0-30mm over 30mm-60mm over 60mm-90mm over 90mm	Dim L=(P-1) \times 3.5+4.4	Dim B	Dim L
	Dim B=(P-1) \times 3.5	± 0.15	± 0.20
	P=1/2 Number of poles (04-48P)	± 0.25	± 0.30
		± 0.30	± 0.40

6. Safety approval:
7. RoHS Compliance
8. Critical dimension:

- HFDH350 xx X xxx
 ① Poles 04-48(2x02-2x24)
 ② Color
 0 Black 3 Orange 5 Green 6 Blue G Pale Gray....
 ③ Custom
 000 K MARK 00K KUNACON MARK....

3	PIN 2	COPPER	TIN PLATED	1/2P
2	PIN 1	COPPER	TIN PLATED	1/2P
1	BODY	PA66 UL94V-0	ALL COLOR	1
ITEM NAME OF PART MATERIAL NOTES				
DWG. W/F. Zhang	DATE 2016.03.10	UNITS: MM	SHEET: 1 OF 1	Tolerance
CHK. W/F. Zhang	DATE 2016.03.10	SCALE: NONE 2.5:1 (.)	REV.: A	X. ± 0.50
APP. Marvin Zhang	DATE 2016.03.31	TITLE: HF-DH350 Series with engagement nose type 90D		X.X ± 0.30
		PART NO. HFDH350xxxxxx		X.XX ± 0.10
		DWG NO. HF-D350-B001		X* $\pm 1^{\circ}$

△	SIGN	DESCRIPTION	CHK.	DATE

KUNA Contact Technology Co., Ltd
<http://www.kunacon.com>