



Technical data

- Nominal voltage: 150V/8A
PITCH: 3.5mm
- Insulation Withstands Voltage:
AC 1300V/MIN
- Insulation Resistance:
1000M Ω or more at DC500V
- Using temperature range: -40C ~ 115C
- Undimensioned Tolerances:

0-30mm over 30mm-60mm over 60mm-90mm over 90mm	Dim B ± 0.15 ± 0.20 ± 0.25 ± 0.30	Dim L ± 0.20 ± 0.25 ± 0.30 ± 0.40
---	---	---

- Safety approval:
- RoHS Compliance
- Critical dimension:

HFDV350 xx x xxx
 ①②③
 ④Poles 04-4(8)(2x02-2x24)
 ⑤Color
 ⑥ 0 Black 3 Orange 5 Green 6 Blue G Pale Gray...
 ⑦ Custom
 ⑧ 000 K MARK 00K KUNACON MARK...

2	PIN	COPPER	TIN PLATED	P				
1	BODY	PA66 UL94V-0	ALL COLOR	1				
MATERIAL								
DWG. W/F.	Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	W/F.	Zhang	DATE	2016.03.10	SCALE:	NONE 2.5:1 (.)	REV.:	A
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HF-DV350 Series with engagement nose type 180D			
PART NO.	HFDV350xxxxxx				X	± 0.50		
DWG NO.	HF-D350-B002				X	± 0.30		
					X	± 0.10		
					X	± 0.10		

△

DESCRIPTION

CHK.

DATE



KUNA Contact Technology Co. Ltd
<http://www.kunacon.com>

DWG NO.

HF-D350-B002

