

# Data Sheet

## (Plug) of Pluggable Terminal Block

**Pitch: 3,50 mm**


**Serie: A14G164**

### Customer Information for special Item

**EDCON Customer : 0**

**Customer Version No. : 0**


# EDCON-COMPONENTS



## Technical Discription

Group UL / CUL	B	C	D
Rated Voltage: (V)	300		300
Rated Current: (A)	10		10
Wire Range:			
Solid: (AWG)	28~16		
Stranged: (AWG)	28~16		
Withstanding Voltage:	1600V/1Min		
<b>Technical Data IEC (VDE)</b>	III	III	II
Contamination Class	3	2	2
Rated Voltage: (V)	160	160	320
Rated Current: (A)	13,4	13,4	13,4
Withstandin Voltage impulse: (KV)	2,5	2,5	2,5
Conductor Cross Section			
Solid: (mm <sup>2</sup> )	0,2~1,5		
Flexible: (mm <sup>2</sup> )	0,2~1,5		
<b>Material:</b>			
Insulation Material:	PA66		
Imflamability:	UL94V-0		
Contacto Material:	Copper Alloy		
surface Plating:	Tin plated		
<b>Other Data</b>			
Pitch: (mm)	3,5		
No of Poles: (P)	2x2 ~2x24		
Stripping Length: (mm)	10~11		
Screw: (Nm)			
Operating Temperature:: (°C)	-40C to +105		
Pin Dimensions (mm)			
PCB Hole Diameter:(mm)			

## Drawing (Dimension in mm)



### (Plug) of Pluggable Terminal Block


Part No.: **A14G164**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.12.2022	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 3		

[www.edcon-components.com](http://www.edcon-components.com)


email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



PCB Layout

Dimensions (mm)



linear dimension (Tolerances Standard GB/T 14486-2008)										
variable range	to	over	over	over	over	over	over	to	over	over
	6	6 to 10	10 to 30	30 to 60	60 to 100	100 to 160	160 to		10 to 100	100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60


<b>(Plug) of Pluggable Terminal Block</b>	
Part No.:	<b>A14G164</b>
Customer:	

DRW:	Jason	CHKD:	Wilson	MATL:	Wilson	TOLERANCE:	Mason	DATE:	04.12.2022
APPD:	Schumi			FINISH:	Jamy		Sheet No.		2 from 3

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



## Ordering Informations

Serie	No. of Pos.	Body Color	Special Function	Approval Code	ROHS	Packing	EDCON Cust. No.	Customer Version		
-------	-------------	------------	------------------	---------------	------	---------	-----------------	------------------	--	--

<b>A14G164</b>	<b>04</b>	<b>PG</b>	<b>N</b>	<b>A</b>	<b>R</b>	<b>B</b>				
----------------	-----------	-----------	----------	----------	----------	----------	--	--	--	--

Pitch  
3,50

<b>04</b> = Number of Pos. Standard 2x2 ~ 2x24 Pos.	<b>PG</b> = Phoenix Green (Standard)	<b>N</b> = No Function	<b>N</b> = NON Approval <b>A</b> = UL /UR Approval Please consult EDCON for available	<b>R</b> = ROHS Conform <b>N</b> = NON ROHS Conform	<b>B</b> = Bulk-Ware <b>I</b> = Individual Package	<b>xxxxxx</b> = Customer Number	<b>xxx</b> = Customer Version ??(Printing)
			<b>B</b> = VDE Approval Please consult EDCON for available				
			<b>C</b> = TÜV Approval Please consult EDCON for available				

<b>(Plug) of Pluggable Terminal Block</b>	
Part No.:	<b>A14G164</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.12.2022
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3