



P.C.Board Layout

**材质 Material:**  
 绝缘体 Insulator: Glass filled PBT UL94V-0, Grey  
 接触件 Contacts: Brass & Phosphor Bronze  
 电镀层 Plating: Contact Gold 1u"Plated and Dip Tin 80u"Plated over Nickel

**电气性能 Electrical Characteristics:**  
 接触电阻 Contact Resistance: 30mΩmax. at DC 100mA  
 绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC  
 耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute  
 工作电流 Current Rating: 2 AMP  
 使用温度范围 Operating Temperature: -55°C~+105°C

A		B		C		D		E		F		G		H		
标记	处数	描述	更改文件号	签字	日期	UNIT	mm	SCALE	PROJECTION	DESIGNED	CHECKED	DRAWING	DRAWING NO.	SHEET SIZE	COMPUTER NO.	REV.
1	2	3	4	5	6	7	8	1:1	第三角投影	设计	审核	黄伟军	9001-01-4	A4	F / outbo / 工程图 / DIN	0
						PRODUCT	DIN41612 C1 Type (3 Row Long)		GENERAL TOLERANCE		DESIGNED		DRAWING NO.		REV.	
						产品名称	欧式C1型332MR-A1公弯座		X.: ±0.3		设计		9001-01-4		1 OF 1	
						序列号	9001-2132 1C 00A		X.X.: ±0.2		制图		SHEET SIZE		SHEET	
						PRODUCT NO	DIN-C1-332MR-A1		X.XX.: ±0.1		审核		COMPUTER NO.		1 OF 1	
						产品号	DIN-C1-332MR-A1		X.XX.: ±0.5°		核准		F / outbo / 工程图 / DIN		0	