


Pitch: 2.50mm(0.098inch)





SPECIFICATIONS

			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 150V	AC 130V
負載電流	Rated Current	Bemessungsstrom	4A	6A
電線線徑	Wire Size	Leitergrößen	28~20AWG	0.2~0.5mm ²
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
端子	Terminal	Stiftmaterial	Brass, Tin plated	
彈片	Sprin	Kable Schutzeinrichur	Stainless strip steel	
端蓋	Cover	Deckel	Polyamide66(UL94V-0)	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
PC板孔徑	PCB Hole Diameter	Lochdurchmesser	φ1.3mm	
UL File No.	E167040			

TABLE

Item No.	A(mm)	A(inch)
MWX100-25002	6.5	0.256
MWX100-25003	9.0	0.355
MWX100-25004	11.5	0.453
MWX100-25005	14.0	0.551
MWX100-25006	16.5	0.650
MWX100-25007	19.0	0.748
MWX100-25008	21.5	0.847
MWX100-25009	24.0	0.945
MWX100-25010	26.5	1.044
MWX100-25011	29.0	1.142
MWX100-25012	31.5	1.241
MWX100-25013	34.0	1.339
MWX100-25014	36.5	1.437
MWX100-25015	39.0	1.535
MWX100-25016	41.5	1.633
MWX100-25017	44.0	1.731
MWX100-25018	46.5	1.829
MWX100-25019	49.0	1.927
MWX100-25020	51.5	2.025
MWX100-25021	54.0	2.123
MWX100-25022	56.5	2.221
MWX100-25023	59.0	2.319
MWX100-25024	61.5	2.421



PCB Layout

