

Pitch: 2.50mm(0.098inch)





### SPECIFICATIONS

			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 150V	AC 130V
負載電流	Rated Current	Bemessungsstrom	4A	6A
電線線徑	Wire Size	Leitergrößen	28~20AWG	0.2~0.5mm <sup>2</sup>
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
端子	Terminal	Stiftmaterial	Brass, Tin plated	
彈片	Spring	Kable Schutzeinrichur	Stainless strip steel	
壓片、端蓋	Lever,Cover	Hebel, Deckel	Polyamide66(UL94V-0)	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
PC板孔徑	PCB Hole Diameter	Lochdurchmesser	φ1.3mm	
UL File No.	E167040			

TABLE

Item No.	A(mm)	A(inch)
MWX101-25002	6.5	0.256
MWX101-25003	9.0	0.354
MWX101-25004	11.5	0.453
MWX101-25005	14.0	0.551
MWX101-25006	16.5	0.650
MWX101-25007	19.0	0.748
MWX101-25008	21.5	0.846
MWX101-25009	24.0	0.945
MWX101-25010	26.5	1.043
MWX101-25011	29.0	1.142
MWX101-25012	31.5	1.240
MWX101-25013	34.0	1.339
MWX101-25014	36.5	1.437
MWX101-25015	39.0	1.535
MWX101-25016	41.5	1.634
MWX101-25017	44.0	1.732
MWX101-25018	46.5	1.831
MWX101-25019	49.0	1.929
MWX101-25020	51.5	2.028
MWX101-25021	54.0	2.126
MWX101-25022	56.5	2.224
MWX101-25023	59.0	2.323
MWX101-25024	61.5	2.421



PCB Layout

