



EDCON-COMPONENTS




Specifications

Current Rating:	3 Ampere
Insulator Resistance:	5000 Megaohm min.
Dielectric Withstanding:	AC 1000V
Operating Temperature:	-40°C to +105°C
Contact Material:	Copper, Alloy
Insulator Material:	Polyester, UL 94V-0
Standard:	P.B.T.
Contact Plating:	Tin, Gold or Selective Plated
Standard:	Gold Flash Overall
Selectiv Plating:	Gold flash plated on contact area / tin plated on solder area

P.C.B Layout



Drawing (dimensions all into mm)



* = no Contact


PIN Header / Single Row / Single Body / Pitch 5,08mm

Part No.: **T51A1061-**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.09.2022
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 3

Customer:

EDCON-COMPONENTS



Pin Code length table free configuration

Order Code	Dimension (mm)		
	A	B	R1
A01	6,00	3,00	1,50
A02	5,80	13,10	1,50
A03	3,50	3,00	1,50
A04	6,70	3,20	1,50
A05	6,90	3,30	1,50
A06	3,00	3,00	1,50
A07	4,00	3,00	1,50
A08	4,50	3,00	1,50
A09	5,00	3,00	1,50
A10	5,50	3,00	1,50
A11	6,00	3,00	1,50
A12	6,50	3,00	1,50
A13	7,00	3,00	1,50
A14	7,50	3,00	1,50
A15	8,00	3,00	1,50
A16	8,50	3,00	1,50
A17	9,00	3,00	1,50
A18	9,50	3,00	1,50
A19	10,00	3,00	1,50
A20	10,50	3,00	1,50
A21	11,00	3,00	1,50
A22	11,50	3,00	1,50

Order Code	Dimension (mm)		
	A	B	R1
A23			
A24			
A25			
A26			
A27			
A28			
A29			
A30			
A31			
A32			
A33			
A34			
A35			
A36			
A37			
A38			
A39			
A40			
A41			
A42			
A43			
A44			

Order Code	Dimension (mm)		
	A	B	R1
A45			
A46			
A47			
A48			
A49			
A50			
A51			
A52			
A53			
A54			
A55			
A56			
A57			
A58			
A59			
A60			
A61			
A62			
A63			
A64			
A65			
A66			


PIN Header / Single Row / Single Body / Pitch 5,08mm

Part No.: **T51A1061-**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.09.2022
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3

Customer:

EDCON-COMPONENTS



Ordering Informations

Serie	No. of Pos.	Construction	Contact Plating	Material	Polarisation Peg	Pin Length Code	ROHS	Packing		
T51A1061-	XX	RT	GO	PB	N	A01	R	BU		

XX = total pin of header	RT = right angle THT	GO = Gold Flash (Standard)	PB =P.B.T (Standard)	N = No	look table page 2	N =NO ROHS	BU = Bulk (Standard)
T0 = Tin plated	GA = 10µ Gold Plating	PY = Polyester UL94V-0	R =ROHS conform			TU = Tube w/o Cap	
GB = 15µ Gold Plating	GC = 20µ Gold Plating	NY = Nylon-6T	TC = Tube w. pic and Place Cap				
S0 = Selectiv Plating Gold Flash / Tin			TY = Tray packing w/o Cap				
TN = Tin Plated			TR = Tape/Reel w. pic and Place Cap				

PIN Header / Single Row / Single Body / Pitch 5,08mm	
Part No.:	T51A1061-
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.09.2022
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3

www.edcon-components.com

email: info@edcon-components.com