



EDCON-COMPONENTS




Specifications

Current Rating:	1 Ampere
Insulator Resistance:	5000 Megaohm min.
Dielectric Withstanding:	AC 1000V
Operating Temperature:	.-40°C to +105°C
Contact Material:	Copper, Alloy
Insulator Material:	Polyester, UL 94V-0
Standard:	P.B.T.
Contact Plating:	Tin, Gold or Selective Plated
Standard:	Gold Flash Overall
Selectiv Plating:	Gold flash plated on contact area / tin plated on solder area
Max. Prozessing Temp.	230°C for 60 seconds




P.C.B Layout



Drawing (dimensions all into mm)



SECTION A-A




PIN Header / Dual Row / Single
Body / Pitch 2,00mm

Part No.: **T51B1014 -**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	23.06.2024
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4

EDCON-COMPONENTS



Pin Code length table free configuration

Order Code	Dimension (mm)		
	A	B	TL
A01	3,80	3,00	8,80
A02	4,60	2,50	9,10
A03	3,90	2,80	8,70
A04	5,00	5,00	12,00
A05	5,15	3,00	10,15
A06	3,90	2,50	8,40
A07			
A08			
A09			
A10			
A11			
A12			
A13			
A14			
A15			
A16			
A17			
A18			
A19			
A20			
A21			
A22			

Order Code	Dimension (mm)		
	A	B	
A23			
A24			
A25			
A26			
A27			
A28			
A29			
A30			
A31			
A32			
A33			
A34			
A35			
A36			
A37			
A38			
A39			
A40			
A41			
A42			
A43			
A44			

Order Code	Dimension (mm)		
	A	B	
A45			
A46			
A47			
A48			
A49			
A50			
A51			
A52			
A53			
A54			
A55			
A56			
A57			
A58			
A59			
A60			
A61			
A62			
A63			
A64			
A65			
A66			


PIN Header / Dual Row / Single Body / Pitch 2,00mm

Part No.: **T51B1014 -**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	23.06.2024
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

Customer:

EDCON-COMPONENTS




Ordering Informations

Serie	No. of Pos.	Construction	Contact Plating	Material	Polarisation Peg	Pin Length Code	ROHS	Packing		
T51B1014 -	XX	ST	G0	PB	N	Axx	R	BU		


XX = total pin of header	ST = straight THT	G0 = Gold Flash (Standard)	PB =P.B.T (Standard)	N = No	look table page 2	N =NO ROHS	BU = Bulk (Standard)
T0 = Tin plated	GD = 3µ" Gold Plating	PY = Polyester UL94V-0	R =ROHS conform			TU = Tube w/o Cap	
GA = 10µ" Gold Plating	GB = 15µ" Gold Plating	NY = Nylon-6T	TC = Tube w. pic and Place Cap				
GC = 20µ" Gold Plating	S0 = Selectiv Plating Gold Flash / Tin		TY = Tray packing w/o Cap				
TN = Tin Plated			TR = Tape/Reel w. pic and Place Cap				

PIN Header / Dual Row / Single Body / Pitch 2,00mm
Part No.: T51B1014 -
Customer:


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	23.06.2024
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4



Soldering Profile for Lead Soldering (P.B.T.)



Soldering Profile for Lead Free Soldering (Nylon 6T)



PIN Header / Dual Row / Single Body / Pitch 2,00mm

Part No.: **T51B1014 -**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	23.06.2024	Customer:
APPD:	Schumi			FINISH	Jamy			Sheet No.	4 from 4	