



# DATA SHEET

## Metallized Polyester Film Capacitor BOX-Type

### Serie: I18014

Width (mm)	<b>17,5</b>	Range <b>683= 0,068µf</b>
Height (mm)	<b>11,0</b>	Voltage <b>401= 400VDC</b>
Thickness (mm)	<b>5,0</b>	
Pitch (mm)	<b>15,0</b>	

**Metallized Polyester Film  
Capacitor BOX-Type**

Serie No.: **I18014**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	30.04.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 4	

# EDCON-COMPONENTS



## Applications

By-passing, blocking, coupling, decoupling  
 Pulse, logic, timing, oscillator circuits  
 Interference suppression in low voltage application (i.e. automotive)


## Features

High reliability  
 Metallized polyester Film,  
 Non inductive winding construction  
 Plastic Case (UL94V-0) epoxy resin

## Specifications

Reference Standard	GB/T 7332 (IEC 60384-2)								
Climatic Category	55/105/56								
Rated Voltage	85°C								
Operating Temperature	-55°C ~ 105°C (+85°C ~ +105°C: decreasing factor 1,25% per °C for Vr(dc))								
Rated Voltage	63V, 100V, 160V, 250V, 400V, 630V,								
Capacitance Range	0,00033µF~ 33,0µF								
Capacitance Tolerance	± 5%(J) , ±10%(K), ±20%(M)								
Voltage Proof	1,6Ur (5s)								
Dissipation Factor	Frequency	Cr ≤ 0,1µF		Cr ≤ 0,1µF					
	1KHz	≤ 1,0%		≤ 1,0%					
	10KHz	≤ 1,5%		≤ 1,5%					
	100KHz	≤ 3,0%							
Insulation Resistance	Ur > 100V	≥30000MΩ, CR≤0,33µF							
	Ur ≤ 100V	≥15000MΩ, CR≤0,33µF (20°C,100V,1min.)							
Maximum Pulse Rise Time (dV/dt): If the working voltage (U) is lower than the rated voltage (Ur), the capacitor can be worked at a higher dV/dt. In this case, the maximum allowed dV/dt is obtain by multiplying the right value with Ur/U.	Ur(V)	dV/dt (V/µs)							
	Pitch	7,5	10,0	15,0	22,5	27,5			
	63	7,5	6	3	2	1			
	100	15	9	5	3	2			
	250	30	20	12	8	5			
	400	40	30	20	10	7			
630	50	40	25	12	--				
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	30.04.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

## Dimensions ( mm )



Case Size	A
W= ±0,4	17,5
H= ±0,4	11,0
T= ±0,4	5,0
P= ±0,4	15,0

<b>Metallized Polyester Film Capacitor BOX-Type</b>	
Part No.:	<b>I18014</b>
Customer:	

# EDCON-COMPONENTS



## Ordering Informations

Serie	Range	Tolerance	Voltage	Case Size Code	Lead Length	Special function	ROHS	Packing Code		
-------	-------	-----------	---------	----------------	-------------	------------------	------	--------------	--	--

<b>I18014</b>	-	<b>683</b>	<b>M</b>	<b>401</b>	<b>A</b>	<b>LL</b>	<b>N</b>	<b>R</b>	<b>BU</b>	
---------------	---	------------	----------	------------	----------	-----------	----------	----------	-----------	--

<b>683=</b> 0,068µf	<b>M=</b> 20%	<b>401=</b> 400VDC	<b>A=</b> Look Size Dimension	<b>LL=</b> Long Lead	<b>N=</b> No function	<b>R=</b> ROHS Conform	<b>BU=</b> Bulk Ware
	<b>K=</b> 10%			<b>L4=</b> ca. 3,50mm		<b>N=</b> NON ROHS Conform	<b>TA=</b> Tape Ammo Pack
	<b>J=</b> 10%						<b>TR=</b> Tape Reel

<b>Metallized Polyester Film Capacitor BOX-Type</b>	
Part No.:	<b>I18014</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	30.04.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



<b>Metallized Polyester Film Capacitor BOX-Type</b>	
Part No.:	<b>I18014</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	30.04.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	