



DATA SHEET

Metallized polypropylene film A.C. capacitor for capacitive divider

Serie: I38001

Code / Range **104= 0,10 μ f**

Code / Volt **231= 230VAC**

Width **13,0 mm**

Height **12,0 mm**

Thickness **6,0 mm**

Pitch **10,0 mm**

**Metallized polypropylene film
A.C. capacitor for capacitive
divider**

Serie No.: **I38001**

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 15.05.2011 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 1 from 4 |

Customer:

EDCON-COMPONENTS



Features

This is specifically designed for applications in serial with the main i.e.: capacitive divider, for example, energy meter, LED driver etc.

Metallized polypropylene

Good self-healing properties, withstanding overvoltage stressing

Long stability of capacitance


Good properties in damp environment

Excellent active and passive flame resistant abilities.

Dimensions

Specifications

| | | | | |
|---|---|-------------|--------------|--|
| Referance Standard | GB/T 14579 (IEC 60384-17) | | | |
| Climatic Category | 55/105/56 | | | |
| Rated Temperature | +85°C | | | |
| Operating Temperature Range | -55°C ~ +105°C | | | |
| | (+85°C to +105°C ; decreasing factor 1,25% per °C for V _R (dc) | | | |
| Rated Voltage | 230VAC | 250VAC | 275VAC | |
| Maximum continious DC voltage | 400VDC | 560VDC | 630VDC | |
| Capacitance Range | 0,033~4,7µF | 0,01~4,7µF | 0,01~2,2µF | |
| Voltage Proof (Between Terminals) | 640VDC (2s) | 900VDC (2s) | 1500VDC (2s) | |
| Capacitance Tolerance | J=5% , K=10%, M=20% | | | |
| Disspation Factor | ≤ 0,0020 (1KHz, 20°C) | | | |
| Insulation Resistance | ≥ 15000MΩ, C _R ≤0,33µF | | | |
| | ≥ 5000s, C _R ≤0,33µF (20°C, 100V, 1min) | | | |
| Pitch Width | from 7,5mm ~ 27,5mm | | | |
| Note: For long lifetime and continious working, please choose 275VAC and upwards voltage. | | | | |



Case Dimension table

| Case Code | W ±0,4 (mm) | H ±0,4 (mm) | T ±0,4 (mm) | P (mm) |
|-----------|-------------|-------------|-------------|--------|
| A | 13,0 | 12,0 | 6,0 | 10,0 |

C ±0,5 (mm)

Standard Length 18~26mm (Size by Size)

Short Lead 4,5mm

d ±0,05 (mm)

d= 0,6mm

**Metallized polypropylene film
A.C. capacitor for capacitive
divider**

Part No.: **I38001**

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 15.05.2011 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 2 from 4 |

Customer:

EDCON-COMPONENTS



Ordering Informations

| Serie | Range | Tolerance | Voltage | Case Code | Pitch Code | Lead Style | Lead Length C | ROHS | Packing Code | |
|-------|-------|-----------|---------|-----------|------------|------------|---------------|------|--------------|--|
|-------|-------|-----------|---------|-----------|------------|------------|---------------|------|--------------|--|

| | | | | | | | | | | |
|---------------|---|------------|----------|------------|----------|----------|----------|-----------|----------|-----------|
| I38001 | - | 104 | M | 231 | A | 4 | N | LL | R | BU |
|---------------|---|------------|----------|------------|----------|----------|----------|-----------|----------|-----------|

| | | | | | | | | |
|--------------------|------------------------|--------------------|-------------------------------|------------------|-----------------------|---------------------------------|----------------------------|-------------------------------|
| 104= 0,10µf | M= 20% Standard | 231= 230VAC | A= look Case Dimension | 4= 10,0mm | N= No function | LL= Long Lead (Standard) | R= ROHS Conform | BU= Bulk Ware |
| | K= 10% | | | | | 45= Lead Length 4,5mm | N= NON ROHS Conform | TB= Tape Box |
| | J= 5% | | | | | | | IV= Individual Package |
| | | | | | | | | |
| | | | | | | | | |

**Metallized polypropylene film
A.C. capacitor for capacitive
divider**

Part No.: **I38001**

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 15.05.2011 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 3 from 4 |

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



**Metalized polypropylene film
 A.C. capacitor for capacitive
 divider**

Part No.: **I38001**

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 15.05.2011 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | 4 from 4 | Customer: |