



DATA SHEET

Metallized polypropylene film A.C. capacitor for capacitive divider

Serie: I38001

Code / Range **334= 0,33 μ f**

Code / Volt **231= 230VAC**

Width **26,5 mm**

Height **15,0 mm**

Thickness **6,0 mm**

Pitch **22,5 mm**

**Metallized polypropylene film
A.C. capacitor for capacitive
divider**

Serie No.: **I38001**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	15.05.2011
APPD:	Schumi			FINISH	Jamy			Sheet No.	1 from 4

Customer:

EDCON-COMPONENTS



Features

This is specifically designed for applications in serial with the main i.e.: capacitive divider, for example, energy meter, LED driver etc.

Metallized polypropylene

Good self-healing properties, withstanding overvoltage stressing

Long stability of capacitance

Good properties in damp environment

Excellent active and passive flame resistant abilities.

Dimensions

Specifications

Referance Standard	GB/T 14579 (IEC 60384-17)			
Climatic Category	55/105/56			
Rated Temperature	+85°C			
Operating Temperature Range	-55°C ~ +105°C			
	(+85°C to +105°C ; decreasing factor 1,25% per °C for V _R (dc)			
Rated Voltage	230VAC	250VAC	275VAC	
Maximum continious DC voltage	400VDC	560VDC	630VDC	
Capacitance Range	0,033~4,7µF	0,01~4,7µF	0,01~2,2µF	
Voltage Proof (Between Terminals)	640VDC (2s)	900VDC (2s)	1500VDC (2s)	
Capacitance Tolerance	J=5% , K=10%, M=20%			
Disspation Factor	≤ 0,0020 (1KHz, 20°C)			
Insulation Resistance	≥ 15000MΩ, C _R ≤0,33µF			
	≥ 5000s, C _R ≤0,33µF (20°C, 100V, 1min)			
Pitch Width	from 7,5mm ~ 27,5mm			
Note: For long lifetime and continious working, please choose 275VAC and upwards voltage.				



Case Dimension table

Case Code	W ±0,4 (mm)	H ±0,4 (mm)	T ±0,4 (mm)	P (mm)
A	26,5	15,0	6,0	22,5

C ±0,5 (mm)

Standard Length 18~26mm (Size by Size)

Short Lead 4,5mm

d ±0,05 (mm)

d = 0,8mm

**Metallized polypropylene film
A.C. capacitor for capacitive
divider**

Part No.: **I38001**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	15.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

Customer:
email: info@edcon-components.com

www.edcon-components.com

EDCON-COMPONENTS



Ordering Informations

Serie	Range	Tolerance	Voltage	Case Code	Pitch Code	Lead Style	Lead Length C	ROHS	Packing Code	
-------	-------	-----------	---------	-----------	------------	------------	---------------	------	--------------	--

I38001	-	334	M	231	A	9	N	LL	R	BU
---------------	---	------------	----------	------------	----------	----------	----------	-----------	----------	-----------

334= 0,33µf	M= 20% Standard	231= 230VAC	A= look Case Dimension	9= 22,5mm	N= No function	LL= Long Lead (Standard)	R= ROHS Conform	BU= Bulk Ware
	K= 10%					45= Lead Length 4,5mm	N= NON ROHS Conform	TB= Tape Box
	J= 5%							IV= Individual Package

**Metallized polypropylene film
A.C. capacitor for capacitive
divider**

Part No.: **I38001**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	15.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



**Metalized polypropylene film
A.C. capacitor for capacitive
divider**

Part No.: **I38001**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	15.05.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4		