





# EDCON-COMPONENTS




## Specifications

Current Rating:	3,0 Ampere
Insulator Resistance:	5000 Megaohm min.
Dielectric Withstanding:	AC 500V
Operating Temperature:	.-40°C to +105°C
Contact Material:	Copper, Alloy
Insulator Material:	P.B.T / PA6T
Standard:	PBT
Contact Plating:	Tin, Gold or Selective Plated
Standard:	Gold Flash Overall
Selectiv Plating:	Gold flash plated on contact area / tin plated on solder area
Max. Prozessing Temp.	230°C for 60 seconds

## Drawing ( dimensions all into mm)




## P.C.B Layout



PIN Header / Tripple Row / Dual Body / Pitch 2,54mm	
Part No.:	<b>T51A1052</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	13.06.2019
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4

# EDCON-COMPONENTS




## Pin Code length table free configuration

Order Code	Dimension (mm)			
	A	B	C	
A01	3,30	4,90	31,80	40,00
A02	5,70	3,30	44,50	53,50
A03				
A04				
A05				
A06				
A07				
A08				
A09				
A10				
A11				
A12				
A13				
A14				
A15				
A16				
A17				
A18				
A19				
A20				
A21				
A22				

Order Code	Dimension (mm)			
	A	B	C	D
A23				
A24				
A25				
A26				
A27				
A28				
A29				
A30				
A31				
A32				
A33				
A34				
A35				
A36				
A37				
A38				
A39				
A40				
A41				
A42				
A43				
A44				

Order Code	Dimension (mm)			
	A	B	C	D
A45				
A46				
A47				
A48				
A49				
A50				
A51				
A52				
A53				
A54				
A55				
A56				
A57				
A58				
A59				
A60				
A61				
A62				
A63				
A64				
A65				
A66				




PIN Header / Tripple Row / Dual Body / Pitch 2,54mm

Part No.: **T51A1052**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	13.06.2019
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

# EDCON-COMPONENTS



## Ordering Informations

Serie	No. of Pos.	Construction	Contact Plating	Material	Plastic Type	Pin Length Code	ROHS	Packing		
<b>T51A1052</b>	<b>XX</b>	<b>ST</b>	<b>G0</b>	<b>PB</b>	<b>2</b>	<b>A01</b>	<b>R</b>	<b>BU</b>		


<b>XX</b> = total pin of header	<b>ST</b> = Straight THT	<b>G0</b> = Gold Flash (Standard 0,25µm)	<b>PB</b> =P.B.T (Standard)	1= Plastic Type 1	look table page 2	<b>N</b> =NO ROHS	<b>BU</b> = Bulk (Standard)
		<b>T0</b> = Tin plated		2= Plastic Type 2			<b>R</b> =ROHS conform
		<b>GA</b> = 10µ Gold Plating	<b>PA</b> = Polyester 6T			<b>TC</b> = Tube w. pic and Place Cap	
		<b>GB</b> = 15µ Gold Plating		<b>TY</b> = Tray packing w/o Cap			
		<b>GC</b> = 20µ Gold Plating		<b>TR</b> = Tape/Reel w. pic and Place Cap			
		<b>S0</b> = Selectiv Plating Gold Flash / Tin					
		<b>TN</b> = Tin Plated					

PIN Header / Tripple Row / Dual Body / Pitch 2,54mm
Part No.: <b>T51A1052</b>
Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	13.06.2019
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4


[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)



Soldering Profile for Lead Free Soldering

Classification Reflow Profile (JEDEC J-STD-020C)



PIN Header / Tripple Row / Dual Body / Pitch 2,54mm	
Part No.:	<b>T51A1052</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	13.06.2019
APPD:	Schumi			FINISH	Jamy		Sheet No.		4 from 4