





**HEAT SHRINKABLE TUBE**

**Applications**

Ultra thin wall and low recovery temperature provide space savings and rapid shrinking. Used for strain relief on high-density connectors and further reduces risk of damage to temperature-sensitive components.

**Operating Temperature**

Operating temperature : -55°C~125°C
Minimum shrink temperature : 60°C
Minimum fully recovery temperature : 100°C

**Characteristics**

Very flexible, highly flame retardant (colors only) Low shrink temperature and rapid shrinking Excellent physical, chemical, and electrical properties.

**Approvals**

UL224 File no. E255532, 125°C VW-1 300V
---

**Colors of Delivery**

Black		

**other Colors of request**



**Ordering Information**

Serie	Size	Color	Length	ROHS	Packing	
<b>N41021</b>	<b>A01</b>	<b>BK</b>	<b>100</b>	<b>R</b>	<b>R</b>	

<b>A01=</b> Size Code	<b>BK=</b> Black	<b>100=</b> 100 Meter	<b>R=</b> Rohs Conform	<b>R=</b> Reel Packing

<b>Heat Shrinktube</b>	
Part No.:	<b>N41021</b>
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	06.06.2007
APPD:	Join			FINISH	Shieh	Sheet	2 from 2