



HEAT SHRINKABLE TUBE

BEFORE SHRINKAGE

Size Code	I.D.	Thickness
A01	1,6	0,15
A02	3,2	0,18
A03	4,8	0,20
A04	6,4	0,22
A05	9,5	0,25
A06	12,7	0,25
A07	19,1	0,35
A08	25,4	0,45
A09	39,0	0,50
A10		
A11		
A12		
A13		
A14		
A15		
A16		
A17		
A18		
A19		
A20		
A21		
A22		
A23		
A24		
A25		
A26		
A27		
A28		
A29		
A30		
A31		
A32		
A33		
A34		
A35		
A36		
A37		
A38		
A39		
A40		
A41		

AFTER SHRINKAGE

I.D	Thickness	Quantity of Reel
0,5	0,45	200 Meter
1,0	0,55	
1,50	0,60	100 Meter
2,0	0,65	
3,00	0,75	50 Meter
4,0	0,80	
6,00	0,90	
8,0	1,20	
13,0	1,25	

Heat Shrinktube	
Part No.:	N41022
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	06.06.2009
APPD:	Join			FINISH	Shieh	Sheet	1 from 2



HEAT SHRINKABLE TUBE

Applications

Designed to provide specially expansion ratio, which is ideal for repairing harnesses or cables, and completely connecting and covering cables, jackets, oversize connectors, and components. It's very suitable for application to irregular, awkward shapes.

Operating Temperature

Operating temperature : -55°C~125°C
Minimum shrink temperature : 70°C
Minimum fully recovery temperature : 100°C

Characteristics

Flame retardant (colors only) Resistant to common fluids and solvents Excellent physical, chemical, and electrical properties Material meet Standard of Sony-S-00259,RoHS

Approvals

UL224 File no. E255532, 125°C VW-1 600V

Colors of Delivery

Black		

other Colors of request



Ordering Information

Serie	Size	Color	Length	ROHS	Packing	
N41022	A01	BK	100	R	R	

A01= Size Code	BK= Black	100= 100 Meter	R= Rohs Conform	R= Reel Packing

Heat Shrinktube	
Part No.:	N41022
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	06.06.2007
APPD:	Join			FINISH	Shieh	Sheet	2 from 2