



HEAT SHRINKABLE TUBE

BEFORE SHRINKAGE

Size Code	I.D.	Thickness
A01	1,6	0,20
A02	2,4	0,25
A03	3,2	0,25
A04	4,8	0,25
A05	6,4	0,30
A06	8,0	0,30
A07	9,5	0,30
A08	12,7	0,35
A09	16,0	0,35
A10	19,1	0,40
A11	25,4	0,45
A12	31,8	0,45
A13	38,1	0,50
A14	50,8	0,55
A15		
A16		
A17		
A18		
A19		
A20		
A21		
A22		
A23		
A24		
A25		
A26		
A27		
A28		
A29		
A30		
A31		
A32		
A33		
A34		
A35		
A36		
A37		
A38		
A39		
A40		
A41		

AFTER SHRINKAGE

I.D	Thickness	Quantity of Reel
0,80	0,43	200 Meter
1,20	0,51	
1,60	0,51	
2,40	0,51	
3,20	0,64	100 Meter
4,00	0,64	
4,80	0,64	
6,40	0,64	
8,00	0,76	50 Meter
9,50	0,76	
12,7	0,89	
15,9	1,02	
19,0	1,02	
25,4	1,14	

Heat Shrinktube	
Part No.:	N41024
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	06.06.2009
APPD:	Join			FINISH	Shieh	Sheet	1 from 2



HEAT SHRINKABLE TUBE

Applications

Unique yellow-green striped color used for identifying earth cables, which applying to wire marking, color coding, electrical insulation of wire harness assemblies. Comply with international electrical ground designation.

Operating Temperature

Operating temperature : -55°C~125°C
Minimum shrink temperature : 70°C
Minimum fully recovery temperature : 110°C

Characteristics

Dual colors for instant identification Permanent tubing colors are superior to conventional ink marking

Approvals

--

Colors of Delivery

Yellow/Green		

other Colors of request

--



Ordering Information

Serie	Size	Color	Length	ROHS	Packing	
N41024	A01	YG	100	R	R	

A01= Size Code	YG= Yellow/Green	100= 100 Meter	R= Rohs Conform	R= Reel Packing

Heat Shrinktube	
Part No.:	N41024
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	06.06.2007
APPD:	Join			FINISH	Shieh	Sheet	2 from 2