



HEAT SHRINKABLE TUBE

Applications

Wide range of applications - tennis rackets, badminton rackets, fishing rods, baseball bats, billiard cue, hockey sticks, industrial hand tools, athletic equipment and various handles. Increased friction and safety on smooth surfaces minimizes slipping.

Operating Temperature

Operating temperature : -55°C~135°C
Minimum shrink temperature : 70°C
Minimum fully recovery temperature : 130°C

Characteristics

Unique surface designed by environment friendly EPDM material for durable abrasion. Flannel decorative surface provides excellent sweat absorption Ratio 50% (2:1) will be conveniently applied in covering irregular shape Avoiding and solving girdle loosen up from handle Innovatory material designed for excellent performance and upgrade product value Different colors and private pattern are available on request for individual design Economical and easy to install, it's well suited for the DIY market

Approvals

AE-AMS-DTL-23053/5 Class 1 & 3

Colors of Delivery

Black	Red	Blue
Yellow	Green	

other Colors of request



Ordering Information

Serie	Size	Color	Length	ROHS	Packing
N41026	A01	BK	100	R	R

A01= Size Code	BK= Black	100= 100 Meter	R= Rohs Conform	R= Reel Packing
	RD= Red			
	BL= Blue			
	YE= Yellow			
	GN= Green			

Heat Shrinktube	
Part No.:	N41026
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	06.06.2007
APPD:	Join			FINISH	Shieh	Sheet	2 from 2