

sleeve







Technical Specification					
Maximum Electrical Ratings:	75℃ / 600V				
Maximum Floatrical Patings	look table				
Maximum Electrical Ratings:					
Terminal Body:	Copper				
Insulation:	Nylon				
Plating:	Tin				
VIM Flared Nylon without copper sleeve					

PIPG-- Pre insulated funnel Nylon insulator with easy entry copper

rechnical Drawing
do a
~

Order Code	AWG	I	dØ	L	Amp				Color
A0	22~16	15,0	1,7	26,0	19A		_	 _	
A1	#8	21,0	4,5	32,0	62A				
A2	#2	32,0	9,4	55,0	160A				
A3	22~6	8,0	1,7	16,0	19A				
A4									
A5									
A6									
A7									Red
A8									
A9									
B0									
B1									
B2						1			
B3						1			
B4						1			

Ordering Information

Serie	Order Code	ROHS	Packing		

N38102	A0	R	BU102		
		-		-	-
		R= ROHS	BU102		

look table	R = ROHS	BU102
look table	conform	1000PCs in
	N = Non	one poly bag
	ROHS	
	conform	

Female long fully insulated terminal					
Part No.:	N38102				
Customer:					
DATE	08 09 2009				

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	08.09.2009
APPD:	Join			FINISH	Shieh	Sheet	1 from 1