




**Technical Specification**

Maximum Electrical Ratings:	75°C / 600V
Maximum Electrical Ratings:	22-16AWG/ 0,5-1,5mm <sup>2</sup> 19A
	16-14AWG/ 1,5-2,5mm <sup>2</sup> 27A
	12-10AWG/4-6mm <sup>2</sup> 48A
Terminal Body:	Copper
Insulation:	
Plating:	Tin

**Technical Drawing**



This Dimension are for 22~16AWG / 0,5~1,5mm<sup>2</sup>

Order Code	Tab (mm)	d2	W	L	F	E	DØ	dØ	Color
A0	#6	3,7	8,0	15,8	7,00	4,80	3,4	1,7	NON Color
A1	#8	4,3	8,0	15,8	7,00	4,80	3,4	1,7	
A2	#10	5,3	8,0	15,8	7,00	4,80	3,4	1,7	
A3	1/4	6,4	11,6	21,8	11,00	4,80	3,4	1,7	
A4									
A5									
A6									
A7									
A8									
A9									
B0									
B1									
B2									
B3									
B4									

**Ordering Information**

Serie	Order Code	ROHS	Packing			
N38120	A0	R	BU102			

look table	R= ROHS conform	BU102 1000PCs in one poly bag
	N= Non ROHS conform	

**Hook end non insulation terminal**

Part No.: **N38120**

Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	08.09.2009
APPD:	Join			FINISH	Shieh	Sheet	1 from 1