




**Technical Specification**

Maximum Electrical Ratings:	75°C / 600V
Maximum Electrical Ratings:	22-16AWG/ 0,5-1,5mm <sup>2</sup> 19A
	16-14AWG/ 1,5-2,5mm <sup>2</sup> 27A
	12-10AWG/4-6mm <sup>2</sup> 48A
Terminal Body:	Copper
Insulation:	
Plating:	Tin

**Technical Drawing**



This Dimension are for 22~16AWG / 1,5~2,5mm<sup>2</sup>

Order Code	Tab (mm)	BØ	bØ	DØ	dØ	L	F	H							Color
A0		7,4	4,0	3,9	2,4	27,5	16,5	11,0							
A1															
A2															
A3															
A4															
A5															
A6															
A7															
A8															
A9															
B0															
B1															
B2															
B3															
B4															

**Blue Insulator**

**Ordering Information**

Serie	Order Code	ROHS	Packing			
<b>N38165</b>	<b>A0</b>	<b>R</b>	<b>BU102</b>			

look table	R= ROHS conform	<b>BU102</b> 1000PCs in one poly bag
	N= Non ROHS conform	

**Bullet shape fully male isolated terminal**

Part No.: **N38165**  
 Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	08.09.2009
APPD:	Join			FINISH	Shieh	Sheet	1 from 1