

# EDCON-COMPONENTS



## Technical Discription


## Drawing

### Features

- Suitable for ESD Protection
- Low Leakage current
- Low inductance and fast response
- Excellent solderability and high heat resistance for either flow or reflow soldering.

### Applications

- LCD dsipace
- Optical Sensor systems
- ECU protection
- I/O protection systems



Size 0402 / Type 1005

Working Voltage		Breakdown Voltage		Clamping Voltage	Transient energy	Peak Current	Capacitance
DC	AC	at 1mA DC		8/20 $\mu$ s 1A	10/10000 $\mu$ s	8/20 $\mu$ s	at 1KHz
VDC (V)	VRMS (V)	VB (V)	Tol. %	VC (V)	ET (J)	I <sub>p</sub> (A)	C (pf)
<b>3,3</b>	<b>2,5</b>	<b>5</b>	<b>± 20%</b>	<b>10</b>	<b>0,02</b>	<b>10</b>	<b>80</b>

Dimension (mm)	
L	1,00 ± 0,20
W	0,50 ± 0,20
H	0,50 ± 0,20
L1	0,20 ± 0,15

**CHIP Varistor Size 0402**

Part No.: **W14002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 3

Customer:

# EDCON-COMPONENTS



## Ordering Informations

Serie	Working Voltage	Tolerance Code	End-Termination	ROHS	Packing			
-------	-----------------	----------------	-----------------	------	---------	--	--	--

<b>W14002</b>	<b>003</b>	<b>M</b>	<b>N</b>	<b>R</b>	<b>TR</b>			
---------------	------------	----------	----------	----------	-----------	--	--	--

<b>003</b> = 3,3VDC	<b>M</b> = ±20%	<b>N</b> = Nickel (Standard)	<b>R</b> = ROHS Conform	<b>BU</b> = Bulk-Ware
	<b>K</b> = ±10%	<b>S</b> = Silber		
	<b>L</b> = ±15%		<b>TR</b> = Tape Reel	

**CHIP Varistor Size 0402**

Part No.: **W14002**


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3

Customer:



**Soldering Profile Curve**

**Classification Reflow Profile (JEDEC J-STD-020C)**



**CHIP Varistor Size 0402**

Part No.: **W14002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3

Customer: