

# EDCON-COMPONENTS



## Technical Discription


## Drawing

### Features

- Suitable for ESD Protection
- Low Leakage current
- Low inductance and fast response
- Excellent solderability and high heat resistance for either flow or reflow soldering.

### Applications

- LCD dsiplace
- Optical Sensor systems
- ECU protection
- I/O protection systems



Size 0805 / Type 2012

Working Voltage		Breakdown Voltage		Clamping Voltage	Transient energy	Peak Current	Capacitance
DC	AC	at 1mA DC		8/20 $\mu$ s 1A	10/10000 $\mu$ s	8/20 $\mu$ s	at 1KHz
VDC (V)	VRMS (V)	VB (V)	Tol. %	VC (V)	ET (J)	I <sub>p</sub> (A)	C (pf)
<b>14</b>	<b>10</b>	<b>18</b>	<b>± 15%</b>	<b>35</b>	<b>0,1</b>	<b>40</b>	<b>360</b>

Dimension (mm)	
L	2,00 ± 0,20
W	1,20 ± 0,20
H	0,80 ± 0,20
L1	0,30 ± 0,20

**CHIP Varistor Size 0805**

Part No.: **W14004**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 3		

# EDCON-COMPONENTS



## Ordering Informations

Serie	Working Voltage	Tolerance Code	End-Termination	ROHS	Packing			
-------	-----------------	----------------	-----------------	------	---------	--	--	--

<b>W14004</b>	<b>014</b>	<b>M</b>	<b>N</b>	<b>R</b>	<b>TR</b>			
---------------	------------	----------	----------	----------	-----------	--	--	--

<b>014= 14VDC</b>	<b>M= ±20%</b>	<b>N= Nickel (Standard)</b>	<b>R= ROHS Conform</b>	<b>BU= Bulk-Ware</b>
	<b>K= ±10%</b>	<b>S= Silber</b>		
	<b>L= ±15%</b>		<b>TR= Tape Reel</b>	

**CHIP Varistor Size 0805**

Part No.: **W14004**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3

Customer:



**Soldering Profile Curve**

**Classification Reflow Profile (JEDEC J-STD-020C)**



<b>CHIP Varistor Size 0805</b>	
Part No.:	<b>W14004</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3