

EDCON-COMPONENTS



This picture are only a example from the product specification. Every further development changing the construction of the case



Features

- Designed for Outdoor signage, decorating or lighting applications
- Constant Voltage Output
- Resin potted and Waterproof
- Aluminium housing
- Complies with CE Standard

Technical Specifications

Input Voltage:	170~250VAC / 50/60Hz
Max. Power:	300 Watt
Output Type:	Constant Voltage
Dimming	No
Built in active PFC:	No
Power Factor:	Low
Efficiency:	80%
AC inrush current (max.):	Cold start, 40A@230VAC
Output Voltage:	24VDC ±5%
Output Current:	12,5A max.
Overload protection:	105%~120% hiccup mode, auto-recovery
Overvoltage Protection:	120% rated output voltage
Withstand voltage:	I/P~O/P; 1,5KVAC, 1 minute
Operating Temperature:	. -25°C ~ +40°C
Installation:	Outdoor waterproof
IP rating:	IP 66
Cooling:	Free air convection
Certifications (standard):	CE
Connection input/output:	Input:0,75mm²x3 (length 180mm) Output 0,75mm²x2 180mm
Dimensions (LxWxH):	ca. 300x150x70mm
Weight:(kg)	ca. 3,3

Waterproof Constant Voltage Power Supply

Part No.: **L40016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.02.2012	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 2		

EDCON-COMPONENTS



Ordering Informations

Serie	Special function	ROHS	Packing							
-------	------------------	------	---------	--	--	--	--	--	--	--

L40016	X	R	S							
---------------	----------	----------	----------	--	--	--	--	--	--	--

X = No function	R = ROHS Conform	S = Standard Packing
------------------------	-------------------------	-----------------------------

Waterproof Constant Voltage Power Supply

Part No.: **L40016**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.02.2012
APPD:	Schumi			FINISH	Jamy			Sheet No.	2 from 2